



# **TK500-v3 Series**

## **LTE-Wi-Fi Router**

<https://www.welotec.com/products/tk500-v3-series>





## DIN Rail Industrial Router TK500-v3 Series



Robust industrial router designed for demanding environments, providing reliable connectivity and integrated cybersecurity features. Five Ethernet Ports, RS-232, RS-485 DIN-Rail mounting and 9 to 36 V DC power supply Integrated Firewall, OpenVPN and IPsec Very compact and rugged housing Fully integrated with Welotec Smart EMS and VPN Security Suite 5 year warranty





#### **4G/LTE support**

Optional 4G/LTE ensures fast data rates and optimal network coverage.



#### **Device Management**

Easy rollout of VPN configurations and certificates to connected Welotec devices (incl. Docker Container).



#### **Secure E2E connection**

Integrated with Welotec VPN Security Suite for easy setup of scalable VPN infrastructures.



#### **Compact housing**

High computing power in a small package.



#### **Cyber Security**

BSI-compliant encryption and unique device identification (e.g. via serial number or IMSI).



#### **DIN-Rail mounting**

Designed to be used in switching cabinets with DIN-Rail mounting.



# Technical Details

## Ethernet Characteristics

<b>Ethernet</b>	5 * 10/100 Mbps isolated Fast Ethernet RJ45 ports (1 WAN Port, 4 LAN ports with VLAN capabilities)
-----------------	--

## Other Interfaces

<b>Serial Interface</b>	1 x RS232, 1 x RS485
-------------------------	----------------------

## Mechanical and Environmental

<b>Dimensions (W x H x D)</b>	127 x 108.2 x 35mm
<b>Weight</b>	460g
<b>Protection</b>	IP30
<b>Housing</b>	Metal
<b>Storage Temperature</b>	-40 up to 85°C
<b>Operating Temperature</b>	-20 up to 70°C
<b>Humidity</b>	5 to 95% (non-condensing)

## Power Characteristics

<b>Voltage</b>	9 ... 36 VDC – over-current protection + reverse polarity protection
<b>Standby Power</b>	120mA-200mA@12V
<b>Working Power</b>	150mA-320mA@12V



**Peak Power** 320mA@12V

## EMC Characteristics

<b>Static</b>	EN61000-4-2, level 3
<b>Radiation Electric Field</b>	EN61000-4-3, level 3
<b>Pulsed Electric Field</b>	EN61000-4-4, level 3
<b>Surge</b>	EN61000-4-5, level 3
<b>Conducted Disturbance Immunity</b>	EN61000-4-6, level 3
<b>Shock Wave Resistance</b>	EN61000-4-12, level 3
<b>Power Frequency Magnetic Field Resistance</b>	EN61000-4-8, horizontal / vertical 400A/m (>level 2)

## Physical Characteristics

<b>Shockproof</b>	IEC60068-2-27
<b>Free Fall</b>	IEC60068-2-32
<b>Vibration Resistance</b>	IEC60068-2-6

## Firmware Characteristics

<b>Firewall</b>	Stateful Packet Inspection, Access Control List, URL Filter
<b>VPN</b>	IPSec (IKEv1 + IKEv2), OpenVPN, WireGuard, ZeroTier
<b>Stability</b>	Watchdogs for Connectivity and Malfunction Recovery, Dual-SIM failover, Link Backup



<b>Device Management</b>	Fully Compatible with SMART EMS - OTA Firmware and Configuration Updates
<b>Remote Access</b>	Fully Compatible with VPN Security Suite for automated setup of distributed VPN infrastructures
<b>Configuration</b>	Configuration via Smart EMS, WebUI, SSH and serial console
<b>Monitoring</b>	SNMP v1/v2/v3 supporting SNMP traps (planned), local and remote System-Logs

## Approvals

<b>CE (EU)</b>	In process
<b>RoHS</b>	Yes
<b>REACH</b>	Yes
<b>FCC</b>	In process
<b>ICES</b>	In process
<b>ECE R10</b>	In process
<b>ECE R118</b>	Yes

## Cellular Characteristics

<b>Cellular Chipset</b>	Quectel EC200A-EU
<b>4G Standard</b>	Cat.4
<b>GSM Bands</b>	B3/ B8
<b>UMTS Bands</b>	B1/ B5/ B8
<b>LTE Bands</b>	FDD: B1/ B3/ B5/ B7/ B8/ B20/ B28 TDD:



	B38/ B40/ B41
<b>Download (max)</b>	150
<b>Upload (max.)</b>	50
<b>SIM card</b>	Dual Nano-SIM
<b>Antenna Connectors</b>	2 * SMA (f)

## WiFi Characteristics

<b>WiFi</b>	2.4 GHz IEEE802.11 b/g/n
<b>WiFi Modes</b>	Client / Access Point
<b>WiFi Security – Client</b>	WPA-PSK/ WPA2-PSK TKIP/AES
<b>WiFi Security – Access Point</b>	WPAPSK/ WPA2-PSK
<b>Antenna connectors</b>	2x SMA (f) RP

## LED

**Power, Status, WAN, WiFi, Signal (3 LEDs)**


Discover our comprehensive documentation and guides to get the most out of our products. On our dedicated „Welotec Documentation Page,“ you'll find detailed manuals, installation instructions, and technical specifications to help you execute your projects efficiently and successfully.  
<https://welotec.com/de/pages/download-service> or

<https://docs.welotec.com/en/latest/>





## Contact us

 +49 2554 9130 00

 [service@welotec.com](mailto:service@welotec.com)

Welotec GmbH  
Zum Hagenbach 7  
48366 Laer, Germany  
[www.welotec.com](http://www.welotec.com)

