

WLAN ACCESS POINTS



Low budget: WLAN technique according 802.11n standard

bintec W150n

- WLAN according IEEE 802.11n, compatible to .11bg
- Single Band Radio 2.4 GHz
- Physical data rates of up to 150 Mbps
- Operation as access point, bridge, WDS, client



bintec W150n

Low budget: WLAN technique according 802.11n standard

The bintec W150n is ideal for small companies or home offices, providing wireless access to the Internet, network printers, or other network components. The W150n operates in the 2.4 GHz band.

The bintec W150n, an affordable entry-level option for 802.11n wireless networking, appeals to users with its extremely small footprint. Ideal for small companies or home offices, the W150n provides wireless access to the internet, network printers, or other network components. The 802.11n device uses the 2.4 GHz band and MIMO 1x1 technology to achieve transmission rates of up to 150 Mbps using 40 MHz channels. The W150n is of course also backwards compatible with 802.11b (11 Mbps) and 802.11g (54 Mbps) WLAN devices.

The bintec W150n operates as an access point, but can also serve as a WLAN client if desired. This configuration enables devices that drivers cannot be installed on and those equipped with only an Ethernet port to quickly and easily connect to the wireless network. Together with a second W150n, the router can also be used as a repeater or to implement a bridge link.

Variants

| | |
|----------------------------------|---|
| bintec W150n (5530000036) | WLAN Access Point, 150Mbit/s, 1x1 Mimo, IEEE802.11bgn, 2,4GHz, 1xETH 10/100Mbit/s, 1 ext. RSMA antenna connector, WPA, WPA2, power supply 230V, 1 x standard antenna with 2 dBi |
|----------------------------------|---|

Features

| Wireless LAN | |
|---|--|
| Operation mode | Selectable: Access Point, Wireless Client (Ethernet Adapter), AP+Repeater (WDS), Bridge, WISP |
| Standards | 802.11bgn (Mimo 1x1, one spatial stream) |
| Frequency | 2.412 to 2.472 GHz |
| Channels | Automode or selectable 1 - 13 |
| Bandwidth | 20/40 MHz |
| Data rates/Modulation .11b/g | Modulation: 11, 5.5, 2 und 1 Mbps (DSSS); 54, 48, 36, 24, 18, 12, 9 and 6 Mbps (OFDM) |
| Modulation .11n | Modulation: MCS0, 1, 2, 3, 4, 5, 6, 7, 32 |
| Datenraten .11n (20MHz / auto guard interval) | MCS0=7.2Mbit/s; MCS1=14.4Mbit/s; MCS2=21.7Mbit/s; MCS3=28.7Mbit/s; MCS4=43.3Mbit/s; MCS5=57.8Mbit/s; MCS6=65.0Mbit/s; MCS7=72.2Mbit/s |
| Datenraten .11n (40MHz / auto guard interval) | MCS0=15.0Mbit/s; MCS1=30.0Mbit/s; MCS2=45.0Mbit/s; MCS3=60.0Mbit/s; MCS4=90.0Mbit/s; MCS5=120.0Mbit/s; MCS6=135.0Mbit/s; MCS7=150.0Mbit/s; MCS32= 6.7 Mbit/s |
| Transfer rate | Automatic fallback or selectable transfer rate |

Wireless LAN

| | |
|------------------------|--|
| Transmit power | max. 17.5dB @ 802.11b; max. 15 dBm @ 802.11g; max. 14 dBm @ 802.11n MCS7 HT40; + 2 dB Antennengewinn |
| Receiver Sensitivity | -85dBm @ 802.11b / 11 Mbit/s; -68dBm @ 802.11g / 54 Mbit/s; -68dBm @ 802.11n MCS7 HT20/40; -82dBm @ 802.11n MCS0 HT20/40 |
| WMM (Wi-Fi Multimedia) | Supported |
| Antenna | 2dBi omni-directional antenna, detachable; at the unit is a RSMA connector (male) |

Security

| | |
|--------------------------------|---|
| Standards | WEP, WPA, WPA2; 802.1x only for AP Mode |
| Wireless Protected Setup (WPS) | Pin Method, Push-Button Method |
| Network Name (SSID) | Up to four SSID defineable |
| Network Name (SSID) Visibility | On/off |
| Intercell Repeating | On/off (allows or disallows the communication between associated Wifi client) |
| Access Control List (ACL) | MAC Addresses defineable as White List or as Black List |
| WLAN on/off | Supported |

Maintenance

| | |
|---------------------------|---|
| Configuration | Web-GUI (http) in English language |
| Configuration Wizard | Yes |
| Dime Manager Support | No |
| WLAN Controller Support | No |
| Firmware Update | Yes |
| Configurations Management | Save/Restore as file |
| Statistics | For each interface separate RX/TX counter |

Hardware

| | |
|-------------------|--|
| LAN Interface | 10/100Base-T Ethernet, Full duplex with Auto MDI/MDIX support; fixed IP Address or DHCP Client (only in AP mode) |
| Power supply | 5V/1A DC via wall adapter |
| Power supply unit | Wide range switched powered wall adapter 100-240V AC 50/60Hz |
| Power consumption | 3 Watt |
| Reset Button | Set the device to back factory settings |
| LEDs | Operation, LAN Link, Wifi active |
| Dimensions | 102 x 71 x 20 mm (length x wide x height) |
| Wall mounting | No |

Hardware

| | |
|-------------------------|--|
| Environment - Operation | 0-50° C max. 90% humidity (not condensing) |
| Environment - Storage | -20-70° C 5-95% humidity |
| Certification | EN60950-1; EN55022; EN55024; EN301489-1 V1.8.1; EN301489-17 V2.1.1; EN300328 V1.7.1; EN301489-7 V1.3.1; EN50385; EuP Directive 2009/278/EC |

Content of Delivery

| | |
|--------------------------|--|
| Antenna | W150n including 2dB antenna |
| Power Supply | Switched powered wall adapter 100-240V (euro plug) |
| Cable | Ethernet cable |
| Documentation | CD Rom with detailed documentation in English language |
| Quick Installation Guide | In German and English language |