

WATCH ID

Ref. IDP 2735 (white) – IDP 2734 (blue)

- ⊗ User-definable Tag's Identifier (RW)
- ⊗ High receiving range: up to 80 meters (open field)
- ⊗ Lifecycle: up to 10 years (according to settings)
- ⊗ IP68 Waterproof
- ⊗ Watch casing*



Technical specifications

Battery power supply	3 VDC – CR2032 Internal battery
Frequency	433.92 MHz
Operating temperature	-30°C to +70°C
Identifier settings	ID code – Emission cycle -Activation/Deactivation
Duty cycle	From 0.22s up to 12hours by programming
Settings & configuration	By SCIEL PROG IR tool and ERW software
Reader's compatibility	SCIEL Reader Family
Battery level management	Specific ID code for low level of battery
Housing	Size: 45 mm x 37 mm – thickness 13mm Weight: 19g Material: Nylon Mounting: two loops 26 mm x 2mm assemble the wristwatch

Standards

EN 301 489 – 3: 2002 V1.4.1¹


EN 300 220 – 2007: V2.1.2

RoHS Certified

¹ Except EN 61000-4-2:1995 + A1:1998 + A2:2001.



*Not supplied bracelet



SARTELCO® SISTEMI SRL

Via Torri Bianche, 1
20871 Vimercate (MB)

Tel. +39- 039- 62905.1 Fax. +39- 039- 62905.99
e-mail sistemi@sartelco.it Web www.sartelco.it