

Antenna-Coach-4NGJs

Coach Roof Antenna with 4x4 MIMO 5G + UN ECE R118 + GNSS

Omnidirectional combo antenna with linear polarization for signal enhancement in 5G, 4G, 3G, 2G . and GPS



Keyfeatures

Cellular	MIMO 5G / LTE / UMTS / GSM
Vehicle	UN ECE R10 / UN ECE R118
GNSS	active

Specifications

Mobile / Cellular	Standard	4 x 5G / LTE / UMTS / GSM 5G Bands: 1, 2, 3, 5, 7, 8, 12, 20, 25, 28, 65, 66, 70, 74, 75, 76, 80, 81, 82, 83, 84, 86 - TDD Bands: 34, 38, 39, 40, 41, 50, 51, 78 LTE Bands: 1, 2, 3, 4, 5, 7, 8, 10, 11, 12, 13, 14, 17, 18, 19, 20, 21, 23, 24, 25, 26, 27, 28, 29, 30, 32, 65, 66, 67, 68, 69, 70, 74, 75, 76, 85 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 45, 50, 51, 53 UMTS Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 19, 20, 21, 25, 26, 32 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40 GSM Bands: 700, 850, 900, 1800, 1900 Frequency 700 - 1900, 3400 - 3800
	Specification	Gain -16 dBi typ. (700 MHz) -8 dBi typ. (800 MHz) ±0 dBi typ. (900 MHz) +1 dBi typ. (1800 MHz) +2 dBi typ. (2100 MHz) +2 dBi typ. (2600 MHz) +5 dBi typ. (3600 MHz) VSWR ≤ 2 typ. Impedance 50 Ohm Radiation omnidirectional
	Connectors	4x SMA male fix connected 3m antenna cable
GNSS	Standards	1 x GPS / Galileo / BeiDou / GLONASS Type active Frequency 1560 MHz - 1625 MHz
	Specification	Gain 25 dBi VSWR 25 dBi Impedance 50 Ohm Radiation omnidirectional
	Amplifier	Power 3 - 5 V Current 13 mA max. Gain 25 dB typ.
	Connectors	1x SMA male fix connected 3m antenna cable
Mechanical	Dimensions	Diameter 112 mm Height 90 mm
	Weight	550 g
	Mounting	Rooftop with screws no ground plane needed
	Color	black
Environment	Operating Temperature	-40°C to +85°C
	Ingress Protection Level	IP69K - Dust-tight, protected against close-range high pressure, high temperature spray downs

Certifications	Compliance Domain	RoHS, REACH, Vehicle according to UN ECE R10, UN ECE R118 Vehicle
Extension Cables	Cellular	4 x fix connected / 3 m / SMA male
Other	Order Code	Antenna-Coach-4NGJs
